

Amendments to the Claims

1-41 Cancelled

10/829239  
10/28/05

42. **(Currently Amended)** A disc drive device supporting at least two types of reading speeds, a high speed and a low speed, capable of driving a disc, reading data from the disc by following a read instruction from a host section, and sending the read data to the host section, the disc drive device comprising:

a processing section operable to read, from the disc at one of the reading speeds, the data corresponding to the read instruction, and additional information related to the data;

a determining section operable to determine, based on the additional information, whether the read data is Real-time data;

a storage section operable to temporarily store the read data; and

a sending section operable to send the data stored in the storage section to the host section in predetermined playback timing, wherein

when the reading speed is currently the low speed, the processing section keeps the reading speed while the determining section determines that the read data is Real-time data.

43. **(Previously Presented)** The disc drive device according to claim 42, wherein

when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when the determining section determines, successively for a predetermined number of times, that the read data is the Real-time data.

44. **(Previously Presented)** The disc drive device according to claim 42, wherein

when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when a data read error occurs.

45. **(Previously Presented)** The disc drive device according to claim 42, wherein

when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed after a data read error occurs and then a predetermined condition is satisfied.

46. **(Previously Presented)** The disc drive device according to claim 45, wherein the predetermined condition is whether data reading has been carried out for a predetermined number of times.

47. **(Previously Presented)** The disc drive device according to claim 45, wherein the predetermined condition is whether data reading has been carried out for a predetermined period.

48. **(Previously Presented)** The disc drive device according to claim 42, wherein when the reading speed is currently the low speed, the processing section changes the reading speed to the high speed when the determining section determines that the read data is not the Real-time data and when a predetermined condition is satisfied.

49. **(Previously Presented)** The disc drive device according to claim 42, wherein the disc includes data areas each including a plurality of zones and a gap provided between the zones, and when the reading speed is currently the low speed, the processing section changes, under a predetermined condition, the reading speed to the high speed while a reading head is passing through the gap, even though the determining section determines that the read data is the Real-time data.

50. **(Previously Presented)** The disc drive device according to claim 48, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined number of times after a data read error was cleared.

51. **(Previously Presented)** The disc drive device according to claim 49, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined number of times after a data read error was cleared.

52. **(Previously Presented)** The disc drive device according to claim 48, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined period after a data read error was cleared.

53. **(Previously Presented)** The disc drive device according to claim 49, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined period after a data read error was cleared.

54. **(Previously Presented)** The disc drive device according to claim 42, wherein the additional information is a recording type bit recorded on a header of a sector that stores the data.

55. **(Currently Amended)** A disc drive device supporting at least two types of reading speeds, a high speed and a low speed, capable of driving a disc, reading data from the disc by following a read instruction from a host section, and sending the read data to the host section, the disc drive device comprising:

- a determining section operable to determine whether the disc has Real-time data thereon based on specific information stored on the disc;

- a managing section operable to set a flag indicating whether the Real-time data exists based on a determination result from the determining section;

- a processing section operable to read, from the disc at one of the reading speeds, the data corresponding to the read instruction;

- a storage section operable to temporarily store the read data; and

- a sending section operable to send the data stored in the storage section to the host section in predetermined playback timing, wherein

- the managing section sets the flag when the determining section determines that the disc has the Real-time data thereon, and

- when the reading speed is currently the low speed, the processing section keeps the reading speed while the flag is set.

56. **(Previously Presented)** The disc drive device according to claim 55, wherein, when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when the determining section determines, successively for a predetermined number of times, that the read data is the Real-time data.

57. **(Previously Presented)** The disc drive device according to claim 55, wherein when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when a data read error occurs.

58. **(Previously Presented)** The disc drive device according to claim 55, wherein when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when a data read error occurs and then a predetermined condition is satisfied.

59. **(Previously Presented)** The disc drive device according to claim 58, wherein the predetermined condition is whether data reading has been carried out for a predetermined number of times.

60. **(Previously Presented)** The disc drive device according to claim 58, wherein the predetermined condition is whether data reading has been carried out for a predetermined period.

61. **(Previously Presented)** The disc drive device according to claim 55, wherein when the reading speed is currently the low speed, the processing section changes the reading speed to the high speed when the flag is not set and a predetermined condition is satisfied.

62. **(Previously Presented)** The disc drive device according to claim 55, wherein the disc includes data areas each including a plurality of zones and a gap provided between the zones, and when the reading speed is currently the low speed, the processing section changes, under a predetermined condition, the reading speed to the high speed while a reading head is passing through the gap, even though the flag is set.

63. **(Previously Presented)** The disc drive device according to claim 61, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined number of times after a data read error was cleared.

64. **(Previously Presented)** The disc drive device according to claim 62, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined number of times after a data read error was cleared.

65. **(Previously Presented)** The disc drive device according to claim 61, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined period after a data read error was cleared.

66. **(Previously Presented)** The disc drive device according to claim 62, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined period after a data read error was cleared.

67. **(Previously Presented)** The disc drive device according to claim 55, wherein the specific information is information representing whether an SLR bit recorded on a read-in area of the disc indicates 1.

68. **(Previously Presented)** The disc drive device according to claim 55, wherein the specific information is information representing whether a DVD\_RTAV directory specified by the UDF format exists on the disc.

69. **(Currently Amended)** The disc drive device according to claim 55, wherein the managing section manages a plurality of flags according to the reading speeds, and can individually-set sets the plurality of flags so that at least one of the reading speeds is not changed when the determining section determines that the disc has the Real-time data thereon.

70. **(Currently Amended)** A disc drive device supporting at least two-types-of reading speeds, a high speed and a low speed, capable of driving a disc, reading data from the disc by following a read instruction from a host section, and sending the read data to the host section, the disc drive device comprising:

an extracting section operable to extract, from the read instruction-coming from the host section, information indicating whether real-time playback is to be carried out;

a processing section operable to read, based on the extracted information, and from the disc at one of the reading speeds, the data corresponding to the read instruction;

a storage section operable to temporarily store the read data; and

a sending section operable to send the data stored in the storage section to the host section in predetermined playback timing, wherein

when the reading speed is currently the low speed, the processing section keeps the reading speed while the information indicates that the real-time playback is to be carried out.

**71. (Currently Amended)** The disc drive device according to claim 70, wherein

when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when the information indicating that the real-time playback is to be carried out comes is extracted successively for a predetermined number of times.

**72. (Previously Presented)** The disc drive device according to claim 70, wherein

when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when a data read error occurs.

**73. (Previously Presented)** The disc drive device according to claim 70, wherein

when the reading speed is currently the high speed, the processing section changes the reading speed to the low speed when a data read error occurs and then a predetermined condition is satisfied.

**74. (Previously Presented)** The disc drive device according to claim 73, wherein

the predetermined condition is whether data reading has been carried out for a predetermined number of times.

**75. (Previously Presented)** The disc drive device according to claim 73, wherein

the predetermined condition is whether data reading has been carried out for a predetermined period.

76. **(Previously Presented)** The disc drive device according to claim 70, wherein when the reading speed is currently the low speed, the processing section changes the reading speed to the high speed when the information does not indicate that the real-time playback is to be carried out and a predetermined condition is satisfied

77. **(Previously Presented)** The disc drive device according to claim 70, wherein the disc includes data areas each including a plurality of zones and a gap provided between the zones, and when the reading speed is currently the low speed, the processing section changes, under a predetermined condition, the reading speed to the high speed while a reading head is passing through the gap, even though the information indicates that the real-time playback is to be carried out.

78. **(Previously Presented)** The disc drive device according to claim 76, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined number of times after a data read error was cleared.

79. **(Previously Presented)** The disc drive device according to claim 77, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined number of times after a data read error was cleared.

80. **(Previously Presented)** The disc drive device according to claim 76, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined period after a data read error was cleared.

81. **(Previously Presented)** The disc drive device according to claim 77, wherein the predetermined condition is whether data reading has been successfully carried out for a predetermined period after a data read error was cleared.

82. **(Previously Presented)** The disc drive device according to claim 70, wherein when an interface to the host section is ATAPI, a streaming bit of a read command is used as the information indicating whether the real-time playback is to be carried out.